



MOUNT a TRX-10S RECEIVER ON a 3 Element FOLDING ANTENNA

MOUNT a TRX-10S RECEIVER ON a 3 Element FOLDING ANTENNA

Directions:

1. Does your TRX-10S Receiver have 4 holes drilled in the bottom of its case? If not, send the receiver to Bluesky Telemetry for drilling. A receiver can become detuned if you open the case to drill holes.
2. Attach the black mounting plate to the antenna *between* the handle and the element nearest the handle.
 - Make sure you can open the antenna element nearest the handle WITHOUT touching the receiver case.
 - Hold the antenna by its handle. Place the black mounting plate on the antenna's main boom, in front of the handle. Mark the place where holes need to be drilled on the boom. Test by placing the receiver on the plate in front of the antenna handle. Make sure you have allowed enough space. Then drill the holes out.
 - Attach the receiver mounting plate to the antenna's main boom. Use the enclosed screws. Check that each screw fits nicely into the beveled holes. There should be a flat surface. No screw heads should stick up.
3. Match the receiver case's **4 bottom holes with the holes** on the plate. Position the receiver **so its face is toward the handle**. Use the **remaining screws to snug the receiver** to the mounting plate.

BlueSky Telemetry

The Corner, Crieff Road, Aberfeldy, Scotland, PH15 2BJ T: +44(0) 1 887 820 816 | F: +44(0) 1 887 820 844
E: info@blueskytelemetry.com | W: www.blueskytelemetry.com

© and made by WMI 2008